

LEO型号

世界上最为紧凑和小尺寸型自走式缠绕机

THE MOST COMPACT AND GENIAL ROBOTIC PALLET WRAPPER
IN THE WORLD

...IT'S THE MACHINE
THAT GOES TO THE PALLET!



尺寸小的优势

- 可在场地受限制场地使用
- 机器尺寸小和机身高度低
- 免维护



高品质的原因

- 高质量生产标准
- 高可靠性
- 高性能



LITTLE THANKS TO

- *RESTRICTED WORKING AREA*
- *COMPACT OVERALL DIMENSIONS AND REDUCED WEIGHT*
- *MAINTENANCE FREE*



GREAT THANKS TO

- *HIGH QUALITY STANDARDS*
- *HIGH FUNCTIONALITY*
- *HIGH PERFORMANCES*



电动操作系统

减少工作面积, 是所有竞争对手中型号占地最小的

固定式立柱

最大包装高度: 2000 mm

微电路板控制

6 种不同程序设定

机械式阻拉膜架

束紧力可调节

免维护电池和密封电池

无需加药水维护, 电源240V - 1Ph

减少机器尺寸和重量

相比其他竞争对手自走式, 机器尺寸小和重量轻

运输方便和节省成本

无重新组装, 节省安装时间和成本

ELECTRIC MANOEUVRING SYSTEM ^{PAT}

Reduces the working area even more in comparison with most robots

FIXED MAST

Maximum pallet-wrapping height: 2000 mm

MICROPROCESSOR LOGIC BOARD ^{PAT}

6 different pre-programmable memorized settings

MECHANIC BRAKE

for film tension regulation

"MAINTENANCE-FREE" AND SEALED BATTERIES

no fill - recharged from standard 240 Volt power supply

REDUCED OVERALL DIMENSIONS AND WEIGHT

Approximately 50% less than most robots

EASY SHIPPING

No parts to be assembled, ready to work

技术参数和描述

- 专利电子控制模式
- 机械阻拉膜架
机器尺寸: 1150 x 780 x 1950 mm
- 2个胶体电池, 免维护
电源充电器: 220 V
- 膜架上升下降速度可调节
- 最大包装高度: 2000 mm
- 最小托盘尺寸: 600 x 600 x 650 (h) mm
- 最大托盘尺寸: 无限制
- 可以在最狭小的区域工作

FEATURES AND TECHNICAL SPECIFICATIONS

- Patented electric manoeuvring system
- Regulation of the film tension through mechanic brake
- Overall indicative dimensions: 1150 x 780 x 1950 mm
- Power supply with 2 gel sealed batteries, maintenance-free
- Power supply (for battery charge) 240 V single-phase
- Film carriage speed: adjustable
- Maximum wrapping height: 2000 mm
- Min pallet dimensions: 600 x 600 x 650 (h) mm
- Max pallet dimensions: without limit
- The pallet-wrapping robot which needs the narrowest area to work